



SPECIAL TUBING / ATFE 1,5:1

High temperature Teflon® tubing



ATFE 1,5:1

Special heat shrink tubing / Teflon® / 260 degrees / 1,5:1

Features:

- Modified Tetrafluoroethylene • Shrink ratio: 1,5:1 • Superior chemical and mechanical performance • Very low friction coefficient • Excellent electrical properties

Approvals:

- Meets: RoHS • Meets: SAE-AMS-DTL-23053/12

Application:

- Operating temperature: -65 °C to +260 °C
- Minimum full recovery temperature: +350 °C
- Longitudinal change: 0 ± 10% max.

Key properties:

- Excellent electrical properties • Excellent chemical resistance • Smoothness
- High dielectric constant • Durable • Application temperature 340°C • UV resistant



Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Standard length in mm
ATFE AWG 20	1,52	0,97	0,30	1220
ATFE AWG 18	1,93	1,17	0,30	1220
ATFE AWG 16	2,36	1,45	0,30	1220
ATFE AWG 14	3,05	1,82	0,30	1220
ATFE AWG 12	3,81	2,26	0,30	1220
ATFE AWG 10	4,85	2,80	0,30	1220
ATFE AWG 8	6,10	3,55	0,38	1220
ATFE AWG 6	7,67	4,40	0,38	1220
ATFE AWG 4	9,40	5,45	0,38	1220
ATFE AWG 2	10,92	6,90	0,38	1220
ATFE AWG 0	11,94	8,56	0,38	1220

For cross references, please see pages 4-5

We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.