



ACSM

Heat Shrink Tubing for boat guard rails

Specially designed and developed shrink tubing for boat guard rails. This tubing is highly UV-resistant and therefore tolerates more sunlight than normal shrink tubing which makes it particularly suitable for boat use.

The optical white is so-called "true colour" and degrades very slowly.

An excellent solution for the protection and renovation of guard rails. Very dense wall thickness ensures strong and long-lasting protection.



Free from harmful substances such as PBB's, PBBO's, PBBE's.

*****This is the genuine and original*****

Type	Dimentions		Thickness fully shrunk	Spol lenght
	Before shrink	After shrink		
12/3	12	3	1,2	200
12/4	12	4	1,5	300

* All dimensions are in millimetres. Spool lengths are in metres. Other dimensions, lengths and colours on request.

Product Information	
Material:	Polyolefin, special designed.
Shrink ratio:	3:1 & 4:1
Shrink temperature:	120°C
Service temperature range:	-55°C to 110°C
Standard colour:	Optical white specially developed.
Standard spools:	See above.



We certify that the values provided are as accurate as possible. Use of these values, however, remains the sole responsibility of the customer and cannot in any way substitute for testing the product under real conditions of use. The user must assess whether this product is suitable for a particular use. KACAB shall not be held responsible for any loss or anomaly resulting from the correct or incorrect use of this product.