

POLYAMIDE PA6 GF30 JACOB REDUCTIONS, PG

Material	Polyamide PA6 GF30
External thread	PG (DIN 40430)
Internal thread	PG (DIN 40430)
Temperature range	-30 °C up to +100 °C
Protection grade	Dependent on the combination with other components
Standard colors	Light grey (RAL 7035), black (RAL 9005)



Typenr.	Connecting thread from - to	Thread length (mm)	Height (mm)	Packing (pcs)
PG9-PG7 PA6 GF30 reduction*	PG9 - PG7	8,0	20,5	100
PG11-PG7 PA6 GF30 reduction	PG11 - PG7	8,0	14,0	100
PG11-PG9 PA6 GF30 reduction*	PG11 - PG9	8,0	22,5	100
PG13,5-PG7 PA6 GF30 reduction	PG13,5 - PG7	9,0	15,0	100
PG13,5-PG9 PA6 GF30 reduction	PG13,5 - PG9	9,0	15,0	100
PG13,5-PG11 PA6 GF30 reduction*	PG13,5 - PG11	9,0	24,0	100
PG16-PG9 PA6 GF30 reduction	PG16 - PG9	10,0	16,0	100
PG16-PG11 PA6 GF30 reduction	PG16 - PG11	10,0	16,0	100
PG16-PG13,5 PA6 GF30 reduction*	PG16 - PG13,5	10,0	27,0	100
PG21-PG11 PA6 GF30 reduction	PG21 - PG11	11,0	16,0	100
PG21-PG13,5 PA6 GF30 reduction	PG21 - PG13,5	11,0	16,0	100
PG21-PG16 PA6 GF30 reduction	PG21 - PG16	11,0	16,0	100
PG29-PG13,5 PA6 GF30 reduction	PG29 - PG13,5	11,0	17,0	50
PG29-PG16 PA6 GF30 reduction	PG29 - PG16	11,0	17,0	50
PG29-PG21 PA6 GF30 reduction	PG29 - PG21	11,0	17,0	50
PG36-PG21 PA6 GF30 reduction	PG36 - PG21	13,0	19,0	50
PG36-PG29 PA6 GF30 reduction	PG36 - PG29	18,0	24,0	50
PG42-PG21 PA6 GF30 reduction	PG42 - PG21	18,0	24,0	25
PG42-PG29 PA6 GF30 reduction	PG42 - PG29	18,0	24,0	25
PG42-PG36 PA6 GF30 reduction	PG42 - PG36	18,0	24,0	25
PG48-PG29 PA6 GF30 reduction	PG48 - PG29	18,0	24,0	25
PG48-PG36 PA6 GF30 reduction	PG48 - PG36	14,0	20,0	25
PG48-PG42 PA6 GF30 reduction	PG48 - PG42	17,0	23,0	25

In addition to our standard range of cable glands and accessories, we can also supply all other Jacob products (on request). For this, we refer you to the website of Jacob GmbH: www.jacob-gmbh.de/en/